



SAR TEST REPORT

Report No: STS1704224H01

Issued for

JIEKE TECHNOLOGY (HK) LIMITED

909B 9/F TWO GRAND TOWER 625 NATHAN RD KLN
HONG KONG

Product Name:	Smart phone
Brand Name:	Blackview
Model Name:	BV8000 Pro
Series Model:	SOLID 4G3
Test Standard:	EN 50360: 2001/A1:2012; EN 62479: 2010;
	EN 62209-1: 2006; EN 62209-2: 2010;
	EN 50566: 2013/AC:2014;
Max. SAR (10g):	Head:0.281 W/kg
	Body:0.731 W/kg

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.



**Test Report Certification**

Applicant's Name: JIEKE TECHNOLOGY (HK) LIMITED
Address: 909B 9/F TWO GRAND TOWER 625 NATHAN RD KLN HONG KONG
Manufacture's Name: JIEKE TECHNOLOGY (HK) LIMITED
Address: 13th Floor, Weidonglong commercial building B, Meilong avenue, Longhua New District, Shenzhen, China.

Product Description

Product name: Smart phone
Trademark: Blackview
Model and/or type reference : BV8000 Pro
Series Model: BV8000 Pro, SOLID 4G3
EN 50360: 2001/A1: 2012; EN 62479: 2010;
Standards: EN 62209-1: 2006; EN 62209-2: 2010;
EN 50566: 2013/AC: 2014;

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the 2014/53/EU RED Directive Art.3.2 requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test:
Date (s) of performance of tests: 03 May. 2017~05 May. 2017
Date of Issue: 06 May. 2017
Test Result: **Pass**

Testing Engineer : 

(Aaron Bu)

Technical Manager : 

(John Zou)

Authorized Signatory : 

(Vita Li)





1. General Information

1.1 EUT Description

Equipment	Smart phone		
Brand Name	Blackview		
Model Name	BV8000 Pro		
Series Model	SOLID 4G3		
Model Difference	Configuring difference		
Hardware Version	S21_V1.1		
Software Version	BV8000Pro-Blackview-V0.1		
Frequency Range	GSM 900: 880.2 MHz to 914.8 MHz GSM1800: 1710.2 MHz to 1784.8 MHz WCDMA Band I: 1922 MHz to 1978 MHz WCDMA Band VIII: 882.4 MHz to 912.6 MHz LTE Band 1: 1920 MHz to 1980 MHz LTE Band 3: 1710 MHz to 1785 MHz LTE Band 7: 2500 MHz to 2570 MHz LTE Band 8: 880 MHz to 915 MHz LTE Band 20: 832 MHz to 862 MHz LTE Band 38: 2570 MHz to 2620 MHz LTE Band 40: 2300 MHz to 2400 MHz WI-FI IEEE 802.11b/g/n: 2412 MHz to 2472 MHz WI-FI IEEE 802.11a/n: 5150 MHz – 5250 MHz Bluetooth: 2402 MHz to 2480 MHz		
Max. Reported SAR(10g):	Mode	Head(W/Kg)	Body(W/Kg)
	GSM 900	0.281	0.731
	GSM 1800	0.049	0.561
	WCDMA Band I	0.038	0.354
	WCDMA Band VIII	0.226	0.401
	LTE Band 1	0.043	0.406
	LTE Band 3	0.049	0.423
	LTE Band 7	0.017	0.171
	LTE Band 8	0.235	0.474
	LTE Band 20	0.107	0.321
	LTE Band 38	0.042	0.165
	LTE Band 40	0.016	0.428
	WIFI	0.114	0.192
Limit	2.0 W/Kg		
Adapter	Input: AC100-240V, 500mA, 50/60 Hz Output: DC 9.0V, 2000mA		
Battery	Rated Voltage: 3.8V Charge Limit: 4.35V Capacity :4180mAh		
Description test modes	SIM 1 and SIM 2 is a chipset unit and tested as single chipset , SIM 1 is used to tested		
Wireless Type:	GSM: GSM Voice, GPRS, EGPRS Class 12; WCDMA: RMC, HSDPA, HSUPA, Release 6; LTE:QPSK,16QAM; WLAN: 802.11 b/g/n; Bluetooth: V3.0+ EDR (GFSK, π /4DQPSK, 8DPSK); Bluetooth: V4.0		
Power control level	GSM900: 5, DCS1800: 0		
Power class	GSM900: 4, GSM1800: 1		



Antenna Specification:	GSM/WCDMA/LTE: PIFA Antenna Bluetooth/WIFI: PIFA Antenna
Operating Mode:	Maximum continuous output

1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required	Actual
Temperature (°C)	18-25	22~23
Humidity (%RH)	30-70	55~65

1.3 Test Factory

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649

FCC Registration No.: 842334;

IC Registration No.: 12108A-1



Appendix C. Probe Calibration And Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※

Multiple pages of
this report is not in
this file.
Please email
[customer@smartwa
lkietalkie.com](mailto:customer@smartwalkietalkie.com) for